



Working pressure 700 Bar

4:1 Factor of safety

Special lengths available on request

D

Hi-Force high pressure hydraulic hoses provide the vital, high quality, safe connection for your hydraulic equipment. Available in black and red and supplied complete with an ergonomically designed protective strain reliever at both ends, Hi-Force high pressure hoses are suitable for working pressures up to 700 Bar with a 4 : 1 factor of safety.



Tip for double acting systems ...

By using black hoses for the advance lines and red hoses [see next page] for the retract lines, identification is made easy and the possibility of incorrectly connected hoses is reduced.

Hose bore is 6.6mm and outside diameter is 12.7mm for all models:



Length Metres	No couplers 3/8" - 18 NPT male fittings both ends	3/8" - 18 NPT male fitting one end with CM1 coupler fitted one end	CM1 male couplers fitted both ends
0.5	HH0.5	HC0.5	HC0.5C
1.0	HH1	HC1	HC1C
2.0	HH2	HC2	HC2C
3.0	HH3	HC3	HC3C
4.0	HH4	HC4	HC4C
5.0	HH5	HC5	HC5C
6.0	HH6	HC6	HC6C
10.0	HH10	HC10	HC10C
12.0	HH12	HC12	HC12C
15.0	HH15	HC15	HC15C
20.0	HH20	HC20	HC20C
25.0	HH25	HC25	HC25C
30.0	HH30	HC30	HC30C