

Hi-Force®

HIGH PRESSURE HYDRAULIC HOSES - RED



Choice of hose end combinations

Hand grip protective strain relievers

Plastic protective end caps included

D

Hose bore is 6.6mm and outside diameter is 12.7mm for all models:

Length Metres	No couplers		3/8" - 18 NPT male fitting		CM1 male couplers	
	3/8" - 18 NPT male fittings both ends		one end with CM1 coupler fitted one end		fitted both ends	
0.5	HH0.5R	HC0.5R	HC0.5CR			
1.0	HH1R	HC1R	HC1CR			
2.0	HH2R	HC2R	HC2CR			
3.0	HH3R	HC3R	HC3CR			
4.0	HH4R	HC4R	HC4CR			
5.0	HH5R	HC5R	HC5CR			
6.0	HH6R	HC6R	HC6CR			
10.0	HH10R	HC10R	HC10CR			
12.0	HH12R	HC12R	HC12CR			
15.0	HH15R	HC15R	HC15CR			
20.0	HH20R	HC20R	HC20CR			
25.0	HH25R	HC25R	HC25CR			
30.0	HH30R	HC30R	HC30CR			

HYDRAULIC OIL



Hi-Force premium grade hydraulic oil is specially formulated for use with Hi-Force hydraulic tools, providing optimum performance throughout all working conditions.

Model number	Capacity litres	For use with
HFO32-1	1	Manually operated pumps
HFO32-5	5	Manually operated pumps
HFO32-25	25	Manually operated pumps
HFO46-1	1	Powered pumps
HFO46-5	5	Powered pumps
HFO46-25	25	Powered pumps